



Medium

COOL 02

Low comfortable full-leather sneaker

Sporty and slip-resistant ESD occupational sneaker made from natural Nappa leather


Upper	Nappa Leather
Lining	Mesh
Footbed	SJ foam footbed
Outsole	Rubber
Safety standard	O2 / ESD, FO, HRO, SRC
Size range	EU 35-48 / UK 3.0-13.0 US 3.0-13.5 / CM 23.0-31.0
Sample weight	0.436 kg
Norms	EN ISO 20347:2012 ASTM F2892:2018




BLK



WHT



Heel energy absorption
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



Forefoot energy absorption
Forefoot energy absorption reduces the impact of jumps or running on the body of the wearer.



Breathable leather upper
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



Oxygrip / SJ Grip
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.

Industries:

Catering, Cleaning, Food & beverages, Medical, Industry, Uniform

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Nappa Leather			
	Upper: permeability to water vapor	mg/cm ² /h	1.38	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	17	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	37.3	≥ 2
	Lining: water vapor coefficient	mg/cm ²	299	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	25600/12800	≥ 400
Outsole	Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	130	≤ 150
	Outsole slip resistance SRA: heel	friction	0.36	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.37	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.18	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.25	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	32	0.1 - 100
	Heel energy absorption	J	24	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.